

DR.TECHN.OLAV OLSEN AS

Global analyses of OO-Star Wind Floater

Håkon S. Andersen

hsa@olavolsen.no



Outline

- Short Company Introduction
- OO Star Wind Floater
- Global Analysis
- Design Process and Structural Design

OUR HISTORY


- Founded 1962 by Dr.techn. Olav Olsen
- From October 2020 part of Artelia Group
- 110 employees (Olav Olsen)
- Artelia Group 5900 employees worldwide
- Main office at Lysaker
- Regional office in Trondheim
- Structural and marine consulting company
- Participates regularly in research and development projects



BUSINESS AREAS


- Buildings
- Infrastructure
- Offshore Oil & Gas
- Ports and Industry
- Renewable Energy
- Damsafety and Water-resources
- Geotechnical Engineering
- Futurum/CFD/Others
- Electrical Engineering
- HVAC/Water and Sanitation

Revenue distributed per business area



RENEWABLE ENERGY


- Coupled analyses
- Design analyses
- Concept development
- Design of foundation and towers
 - Bottom-fixed and floating
 - Concrete and steel
 - Geotechnics
- Design of mooring and anchors
- Cost and plan
- 3. party verification



OO-Star Wind Floater

- Developed by Dr.techn. Olav Olsen
- IPR's owned by Floating Wind Solutions AS


Selected references Renewable Energy




HYWIND SCOTLAND



OO-STAR WF DEVELOPMENT




WAVEROLLER




INNOVATIVE MOORING SYSTEMS




HYWIND TAMPEN



REDWIN



OFFSHORE WIND GBS



SFT JACKET

Dr.techn. Olav Olsen

Capabilities Offshore wind

> Substructures

- Bottom fixed and floating
- Steel and concrete
- Concept development
- Design and analysis (ShellDesign)
- Geotechnics

> Mooring and anchors

- System configuration
- System design
- Geotechnics

> Installation

- Method development
- Installation concepts


> Fully coupled simulations:

- SIMA
- 3DFloat
- OrcaFlex
- (Deeplines, Ashes, Fast)

> Cost models

- Fabrication and Installation
 - Substructure
 - Mooring
 - Anchors





> Third party verification






OO-STAR WIND FLOATER

OLAV OLSEN – OFFSHORE WIND




THE OO-STAR WIND FLOATER HISTORY

- > Few realistic WTG floaters before 2010
- > HiPRWind (2010) – questions to scalability and fatigue
- > OO-Star Wind Floater developed 2010/11, presented at ONS2012
- > Preferred concept (steel) for EU project Floatgen – Acciona part 3 MW WTG
- > NFR project 2013-2014: Designed for 6MW, WD 100 m, North Sea
- > LIFES50+ 2015-2018: Up-scaling to 10 MW, WD 70-130 m, Hs=7.0 -15.6 m
- > Flagship 2020->: Full-scale demonstrator of the concept




BENEFITS OF CONCRETE

- Robust
 - Fatigue properties
 - Impact loads
 - Design changes
- Good scaling with increased size and loads
- No corrosion for main load bearing structure
- Long design life
- Virtually maintenance-free




POTENTIAL AREAS AND MARKET

Figure 1.1.1. Sea depth around Europe (DNV-GL, 2014)





OO-STAR WF CAN ACCOMMODATE LARGE TURBINES

...FAVOURABLE SCALING DECREASES COST PR MW






MOORING SYSTEM

- > Mooring system is site specific, but several options have been used in previous studies.
 - 3-line catenary system
 - 3-line semi taught system (Chain, polyester and clump weight)
 - 6-line system
- > Mooring attachment at top of corner columns
 - Passive connection – no winch



COST REDUCTION THROUGH INDUSTRIALISATION






GLOBAL ANALYSIS

COUPLED ANALYSIS – SIMULATION OVERVIEW


- > Time domain simulations
- > 1 to 3 hours simulation length
- > 10+ seeds per extreme case
- > Irregular sea states with linear waves
- > Turbulent wind fields



COUPLED ANALYSES – EXTERNAL LOADS




COUPLED ANALYSES - TURBINE




Turbine Model;

- Blade Element Momentum Theory (rotor response)
- Beam elements for components
- Mechanical Components
- Control System

COUPLED ANALYSES - TOWER




COUPLED ANALYSES - FLOATER




Floater Model – Alternative 1;
• Morsion Theory
• Flexible Beam Elements

Floater Model – Alternative 2;
• Potential Theory and Drag Elements
• Rigid body floater

COUPLED ANALYSES - MOORING



COUPLED ANALYSIS – TYPICAL ANALYSIS





CALIBRATION



- > Model Tests:
 - RCN project
 - Lifes50+

- > Reference literature:
 - DNV-RP-C205 Environmental Conditions and Environmental Loads
 - DNV-OS-E301 Position Mooring

- > Analyses:
 - CFD
 - Second Order Potential Theory



CALIBRATION EXAMPLE - CFD



LOAD CASES (DNV-ST-0437)

Table 4-3 Design load cases


Design Situation	DLC	Wind Condition	Marine Condition				Other Conditions:	Type of Analysis		Partial safety factor
			Waves	Wind and wave directionality	Sea Currents	Water Level		Onshore	Offshore	
1) Power Production:	1.1	NTM $V_{in} < V_{hub} < V_{out}$	NSS $H_s = E[H_s V_{hub}]$	COD, UNI	NCM	MSL	For extrapolation of extreme loads (offshore – only RNA)	U	U	N (1.25)
	1.2	NTM $V_{in} < V_{hub} < V_{out}$	NSS Joint prob. distribution of H_{sr}, T_{pr}, V_{hub}	MIS, MUL	No Currents	NWLR or \geq MSL		F/U	F/U	F/N
	1.3	ETM $V_{in} < V_{hub} < V_{out}$	NSS $H_s = E[H_s V_{hub}]$	COD, UNI	NCM	MSL		U	U	N
	1.4	ECD $V_{hub} = V_r - 2 \text{ m/s}, V_r, V_r + 2 \text{ m/s}$	NSS $H_s = E[H_s V_{hub}]$	MIS, wind direction change	NCM	MSL		U	U	N
	1.5	EWS $V_{in} < V_{hub} < V_{out}$	NSS $H_s = E[H_s V_{hub}]$	COD, UNI	NCM	MSL		U	U	N
	1.6	NTM $V_{in} < V_{hub} < V_{out}$	SSS $H_s = H_{s,SSS}$	COD, UNI	NCM	NWLR		-	U	N
	1.7	NTM $V_{in} < V_{hub} < V_{out}$	NSS Joint prob. distribution of H_{sr}, T_{pr}, V_{hub}	MIS, MUL	No Currents	NWLR or \geq MSL	Ice formation	F/U	F/U	F/N

Design Situation	DLC	Wind Condition	Marine Condition				Other Conditions:	Type of Analysis		Partial safety factor
			Waves	Wind and wave directionality	Sea Currents	Water Level		Onshore	Offshore	
6) Parked (standing still or idling)	6.1	EWM $V_{hub} = V_{ref}$	ESS $H_s = H_{s,50}$	MIS, MUL	ECM $U = U_{50}$	EWLR	Yaw misalignment of ± 8 deg Possible yaw slippage	U	U	N
	6.2	EWM $V_{hub} = V_{ref}$	ESS $H_s = H_{s,50}$	MIS, MUL	ECM $U = U_{50}$	EWLR	Loss of electrical network Yaw misalignment of $\pm 180^\circ$	U	U	A
	6.3	EWM $V_{hub} = V_1$	ESS $H_s = H_{s,1}$	MIS, MUL	ECM $U = U_1$	NWLR	Extreme yaw misalignment Yaw misalignment of ± 20 deg	U	U	N

IMPORTANT LOAD EFFECTS

- > Environmental
 - Wave loads
 - First order
 - Second order
 - Slamming
 - Current loads
 - Aerodynamic loads


- > Accidental:
 - Ship Impact






DESIGN PROCESS AND STRUCTURAL DESIGN

MAIN PROCESS – CONCEPTUAL STUDIES





STRUCTURAL ANALYSES – OVERVIEW



LOCAL MODELS


- > Used to verify chosen geometry and find final reinforcement intensity in the substructure
- > Loads are based on the fully coupled simulations
 - Simultaneously acting beam section forces from fully coupled analysis combined with hydrodynamic and hydrostatic pressure



OTHER MODELS

- > WASIM model:
 - Used for validation of hydrodynamics
 - Air gap (idling)
 - (Validation of design forces in WADAM and SIMA)

- > WADAM -> SIMA -> WASIM
 - Supported by the software
 - Currently being tested
 - Expected to be rather complicated and computationally challenging.



CHALLENGES

- > A significant amount of manual work needed to calibrate models
- > Defining consistent and correct design forces for complex areas
- > Representative hydrodynamic pressure in design models

THANKS FOR YOUR
ATTENTION

FOR FURTHER INFORMATION
PLEASE VISIT OUR WEBSITE!

www.olavolsen.no



Disclaimer & copyright

Disclaimer

Dr.techn. Olav Olsen provides no warranty, expressed or implied, as to the accuracy, reliability or completeness of the presentation. and neither Dr.techn. Olav Olsen nor any of its directors or employees will have any liability to you or any other persons resulting from your use.


Copyright

Copyright of all published material including photographs, drawings and images in this presentation remains vested in Dr.techn. Olav Olsen and third party contributors as appropriate. Accordingly, neither the whole nor any part of this document shall be reproduced in any form nor used in any manner without prior permission and applicable acknowledgements. No trademark, copyright or other notice shall be altered or removed from any reproduction.




Backup Slides

PROPOSED PROCESS FOR DETAILED DESIGN




FLOATING OFFSHORE WIND – OUR EXPERIENCE

38



Hywind
Hydro/Equinor



HiPRWind
FP7 EU project





OO-Star Wind Floater
Developed by OO,
owned by FWS

Access and Guide Tubes



ACCESS & GUIDE TUBES

GANGWAY WORKING AREA

- Motion compensation in 4 degrees of freedom
 - Luffing, telescoping, slewing and heaving
- Vertically heave compensation on hinge point
 - Eliminates angle on gangway during operation
- Elevator inside tower syncs the heave compensation of the hinge point



ACCESS SYSTEM - ALTERNATIVE





FLAGSHIP Project

FLoAtinG offSHore wInd oPtimization for commercialization



This project has received funding from the European Union's Horizon 2020 Research And Innovation programme under Grant Agreement N° 952979

Håkon Andersen
Dr.techn.Olav Olsen AS
Email hsa@olavolsen.no



What is FLAGSHIP?



Main objective:

To **reduce** the Levelized Cost of Energy (LCOE) for **floating offshore wind** to the range 40-60 €/MWh by 2030.

Project is based on a **Consortium** created to participate in the European programme **Horizon 2020**, with a full-scale turbine >10 MW in site and environmental conditions comparable to the future potential projects.

Awarded with a **25 MM €** Grant from the European Commission (EC).

Consortium

International consortium lead by **Iberdrola** and including companies and institutions from 5 different countries:

- Spain
- Norway
- Denmark
- Germany
- France

Multi-disciplinary profile of the partners to offer an appropriate balance.




Project overview

- FLAGSHIP will develop and fabricate the first **10+ MW** Floating Offshore Wind Turbine (FOWT).
- Will be assembled on a **floating semi-submersible concrete** structure in the **Norwegian North Sea**.
- The starting point for large-scale 500MW+ commercial floating offshore wind farms of the future
- Project Schedule 2020-2024



Key Technical Areas of the project



Demonstrator Unit in brief

- Floater – Concrete/Steel hull (one off)
 - Designed by Olav Olsen
 - Engineering by Olav Olsen and Aker Solutions
 - Procurement, Fabrication and Installation by Aker Solutions
 - Will be fabricated in a dry dock on the west-coast of Norway
- Mooring System – Catenary chain system (200 m WD)
 - Designed by Olav Olsen
 - Procurement and Installation by Aker Solutions
- Cable IAC – Flexible cable to Zephyros is Base Case
 - Designed and supply by Unitech
- The FLAGSHIP demonstrator will be installed at the Marine Energy Test Centre (MET) in the Norwegian North Sea.

